

PRODUCT DATA SHEET

Sika ViscoFlow[®]-3000 (GB)

High range water reducing/superplasticising concrete admixture with fast adsorption characteristics

PRODUCT DESCRIPTION

Sika ViscoFlow[®]-3000 (GB) is a liquid admixture for concrete based on unique polycarboxylate polymer technologies. Sika ViscoFlow[®]-3000 (GB) is designed as a high range water reducer or superplasticiser. It is particularly suited for use in concretes that require low water/cement ratios and / or high water reductions. The product provides fast adsorption resulting in highly efficient dispersion and potential reduction in mixing time.

USES

Sika ViscoFlow[®]-3000 (GB) is a unique product that is suitable for the production of readymix concrete

- Ideally suited for use in Self-Compacting Concrete (SCC) & flowing screeds
- Suitable for use across a broad range of consistence classes from S3 - SF3
- High-performance concrete
- High-rise concrete
- Slipform concrete
- Improved effectiveness in higher ambient temperatures

PRODUCT INFORMATION

Chemical Base	Modified polycarboxylate
Packaging	1000lt IBC, 20lt container
Appearance / Colour	Clear / straw
Shelf Life	12 months from date of production if stored properly in undamaged containers.
Storage Conditions	Store in dry conditions at temperatures between +5°C and +25°C. Protect from direct sunlight and frost.
Specific gravity	1.06kg/l (at +20°C)

CHARACTERISTICS / ADVANTAGES

High range water reductions resulting in higher strengths & densities

- Improved mixing times
- Improved cohesion properties
- Improved early & ultimate strengths
- Excellent placement characteristics
- Improved rheology
- Improved durability
- Reduced segregation & bleeding
- Reduced drying shrinkage
- Reduced mix costs

APPROVALS / STANDARDS

Conforms to the requirements of BS EN 934-2 tables 3.1 & 3.2.

DoP 14836904, certified by Factory Production Control Body 1029 and provided with the CE mark

DoP 63769647, certified by Factory Production Control Body 0120 and provided with the UKCA mark

pH-Value	4.5 (+/-1.0)
Total Chloride Ion Content	<0.1% w/w (chloride free)
Equivalent Sodium Oxide	<0.25% w/w (alkali content)

TECHNICAL INFORMATION

Specific Advice	Freezing Point: +1°C Air Entrainment: Negligible, minimal increase Effect on Setting: Extension to normal setting time Effect of Overdosing: Increased workability and segregation
Recommended Dosage	0.5 - 1.5% by weight of cement
Compatibility	Sika ViscoFlow®-3000 (GB) may be combined with many other Sika products. Important: Always conduct trials before combining products in specific mixes and contact our Technical Service Department for information and advice about any specific combinations.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

Application Method / Tools

- The standard rules of good concreting practice, concerning production and placing, are to be followed.
- Laboratory trials shall be carried out before concreting on site, especially when using a new mix design or producing new concrete components.
- Fresh concrete must be cured properly and curing applied as soon as possible.

Notes on Application / Limitations

When using Sika ViscoFlow®-3000 (GB) a suitable mix design has to be taken into account and local material sources shall be trialled.

- Sika ViscoFlow®-3000 (GB) shall not be added to dry cement.

- Excessive water addition or overdosing may cause bleeding or segregation.
- Support from our Technical Service Department is recommended.
- Frost: If frozen and / or if precipitation has occurred, Sika ViscoFlow®-3000 (GB) may be used after thawing slowly

DISPENSING

Sika ViscoFlow®-3000 (GB) should be dispensed through suitable calibrated dosing equipment. Sika ViscoFlow®-3000 (GB) is added to the gauging water or added with it into the concrete mixer.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Sika ViscoFlow®-3000 (GB)
May 2021, Version 02.01
021301011000003302

SikaViscoFlow-3000GB-en-GB-(05-2021)-2-1.pdf