

---

# Sika<sup>®</sup> WT200-P

---

## DECLARATION OF PERFORMANCE

### No. 00941088

---

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	00941088
2	<b>INTENDED USE/S</b>	BS EN 934-2 Water resisting concrete admixture according to BS EN 934-2 (Table 9)
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 2+
6a	<b>HARMONISED STANDARD:</b>	BS EN 934-2
	Notified body/ies:	0086

#### Declaration of Performance

Sika(R) WT200-P  
00941088  
2018.01 , ver. 3  
0086

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Chloride Ion content	Max 0.10% by wt	System 2+	BS EN 934-2
Alkali content	Max 4.0% by wt	System 2+	
Capillary absorption	Tested for 7 days after 7 days curing: test mix ≤50% by mass of control mix.	System 2+	
Compressive strength	At 28 days: test mix	System 2+	
Air content	Test mix ≤ 2% by volume above control mix	System 2+	
Corrosion behaviour	Contains only substances according to EN 934-1 Annex A.1	System 2+	
Dangerous substances	NPD	System 2+	

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : John Eustace  
 Function: Product Manager  
 At Welwyn Garden City on 06 January 2018

Name : Tom Forsyth  
 Function: Target Market Manager  
 At Welwyn Garden City on 06 February 2018




End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

Sika(R) WT200-P  
 00941088  
 2018.01 , ver. 3  
 0086





15

Sika Services AG, Zurich, Switzerland

DoP No. 00941088

BS EN 934-2

Notified Body 0086

Water resisting concrete admixture according to BS EN 934-2 (Table 9)

Chloride Ion content	Max 0.10% by wt
Alkali content	Max 4.0% by wt
Capillary absorption	Tested for 7 days after 7 days curing: test mix $\leq$ 50% by mass of control mix.
Compressive strength	At 28 days: test mix
Air content	Test mix $\leq$ 2% by volume above control mix
Corrosion behaviour	Contains only substances according to EN 934-1 Annex A.1
Dangerous substances	NPD

<http://dop.sika.com>

**Declaration of Performance**

Sika(R) WT200-P  
00941088  
2018.01 , ver. 3  
0086



---

## **ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

---

### **LEGAL NOTE**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

---

**Sika Limited**  
Watchmead  
AL7 1BQ Welwyn Garden City  
United Kingdom  
[www.sika.com](http://www.sika.com)

### **Declaration of Performance**

Sika(R) WT200-P  
00941088  
2018.01 , ver. 3  
0086